

**Support Bulletin-SB-25-10044**

**Date-5.20.2025**

**Title: Honda IGX 390 Fuel Filter Installation**

**Product Line: Spray Tender**

**Model: QuickDraw**

**Level: Public**

**Author(s):Andy Boyle**

**Revision Letter: A**



**Overview:** Click or tap here to enter text.

The IGX 390 has two screens installed to reduce dirt and debris from clogging the carburetor. (One in the fuel tank and one on the carburetor)

Users who transport or utilize the Honda IGX 390 in dusty environments can install an inline fuel filter between the fuel tank and the carburetor.

Fuel Filters can be purchased at your local hardware store or online. It's best to perform this procedure when the gas tank is empty.

Note: failure to drain fuel prior to performing step 2 will result in fuel draining from the fuel tank.

For best results utilize a fuel filter:

- That has ¼" Inlet and outlet connections
- With an ability to remove particles 40 microns or less
- With hose clamps

See Next Page for instructions

1. Remove 2 Phillips head screws and the black plastic Honda cover.
2. Cut hose in between the fuel tank and carburetor and remove protective sheath.
3. Install a fuel filter with arrow pointing towards the carburetor. Use clamps to secure filter in hose and prevent future leaks.
4. Reinstall black plastic Honda cover and the 2 Phillips head screws.

