


# 396-001360

### Tank Mounting Instructions 3S3000 30' Drill 400 Gallon Elliptical Tank

**Drill Manufacturer:** 




Kit Number: 551-04-100500





## Parts List and Exploded View

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	727-01-HE00400	Elliptical Tank - 400 Gallon	1
2	450-1058A1	Rear Bracket WA 30' & 40' Great Plains	1
3	380-1042	5/8" x 6" x 7-1/2" Square Bend U-Bolt	4
4	421-1333A2	400 Gallon Elliptical Cradle	1
5	450-1969A1	GP 3S3000 Front Support WA	1
6	380-1043	5/8" x 6" x 11-1/2" Square Bend U-Bolt	1
7	300-100500-5	5/8" x 5" HCS G5	8
8	323-10	5/8" Flange Nut	8
9	330-10	5/8" Flat Washer	8
10	525-3000	3" Tank Strap Kit for 400 - 1000 gal tank	2



396-001360 - Great Plains 30' 400 Gallon Tank Mounting


Page 2 © 2014 – 2022 SurePoint Ag Systems, Inc.

Revised: 6/23/2022




### Step by Step Instructions

- 1. Loosely u-bolt rear stand to drill, centered on the center drill box. Note that vertical tubes are offset to the rear of the drill.
- 2. Loosely u-bolt front stand to drill in location shown.



- 3. Set cradle on stands and bolt down using 5/8" bolts in locations shown above. The front stand may be adjusted forward or backwards as necessary.
- 4. Once cradle is in place, tighten all bolts.
- 5. Set and strap tank in place on cradle.




Revised: 6/23/2022


Page 3 © 2014 – 2022 SurePoint Ag Systems, Inc.



#### Optional/Related Items



PumpRight Bracket Kit Kit Number: 515-203200 Instruction sheet: 396-2613Y1



Tower Bracket Kit
Kit Number: 511-100850
Instruction sheet: 396-2648Y1

Revised: 6/23/2022

Tank Fill Kit: 555-101350

**Tower Discharge Kit: 556-1001** 

PumpRight Discharge Kit: 520-00-103600

Instruction Sheet: 396-2645Y1





#### Optional/Related Items

**Manifold Kits:** 

Instruction sheet for this kit: 396-2618Y1

**553-04-30000:** 30' 7.5" spacing **553-04-30500:** 30' 10" spacing





#### Stainless Steel Tubes:

270-54HD (shown at left) 270-54 270-GP10SERIESHD

Note: When tubes are installed on the HD openers, the seed flapper must be removed.

Revised: 6/23/2022