



## 396-2894Y1

John Deere 2410C 15' Main Frame/40'-0" or 42'-3" 12" Row Spacing 400 & 500 Gallon Elliptical Tank Mounting Instructions

Kit Number: 528-01-450150 (400 Gallon Tank)



Kit Number: 528-01-450160 (500 Gallon Tank)



396-2894Y1 - John Deere - 2410C Tank Mounting Instructions

Page 1 © 2015-2022 SurePoint Ag Systems, Inc.


Revised: 5/25/2022



Parts List and Exploded View

## Kit Number: 528-01-450150 (400 Gallon Tank)

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	420-2835Y1	JD 2410C - 400/500 Gal Tank Stand	2
2	421-1333A2	400 Gallon Elliptical Cradle	1
3	727-01-HE00400	Elliptical Tank - 400 Gallon	1
4	380-1033	3/4" x 4" x 8-1/2" Square Bend U-Bolt	8
5	300-100800-5	5/8" x 8" Bolt G5	10
6	323-10	5/8" Flange Nut	10
7	525-3000	3" Tank Strap Kit for 400 - 1000 gal tank (one strap per kit)	2






Parts List and Exploded View


## Kit Number: 528-01-450160 (500 Gallon Tank)

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	420-2835Y1	JD 2410C - 400/500 Gal Tank Stand	2
2	421-1329A2	500 Gallon Elliptical Cradle	1
3	727-01-HE00500SYSS	Elliptical Tank - 500 Gallon - Yellow	1
4	380-1033	3/4" x 4" x 8-1/2" Square Bend U-Bolt	8
5	300-100800-5	5/8" x 8" HCS G5	10
6	323-10	5/8" Flange Nut	10
7	525-3000	3" Tank Strap Kit for 400 - 1000 gal tank (one strap per kit)	2






## Step by Step Instructions



- 1. Mount the Front Tank Stand (420-2835Y1) with the supplied Square Bend U-bolts (380-1033) as shown in picture above. Refer to 'Detail A' below for approximate locations of where Tank Stand needs to be mounted per specific Tank Kit. Make sure the slotted holes on the top of the Tank Stand are toward the Rear of the Implement. Do not fully tighten U-bolts to allow for adjustment in Step 3.
- 2. Mount the Rear Tank Stand (420-2835Y1) with the supplied Square Bend U-bolts (380-1033) as shown in picture above. Refer to 'Detail A' below for approximate locations of where Tank Stand needs to be mounted per specific Tank Kit. Make sure the slotted holes on the top of the Tank Stand are toward the Front of the Implement. Do not fully tighten U-bolts to allow for adjustment in Step 3.
- 3. Mount the Tank Cradle 421-1333A2 (400 Gallon) or the 421-1329A2 (500 Gallon) to the Tank Stands as shown in picture above with the provided 5/8" Bolts (300-100108-5) and Flange Nuts (323-10). Fully tighten all Nuts and U-bolts.



396-2894Y1 - John Deere - 2410C Tank Mounting Instructions Page 4 © 2015-2022 SurePoint Ag Systems, Inc. Revised: 5/25/2022